3-POINT HITCH CULTIVATOR

Versatile & Tough 3-Point Hitch Cultivator



MODEL 1000 CULTIVATOR

- 5.25' (7 shanks) standard width, also available in 6.75' (9 shanks) and 8.25' (11 shanks)
- 9-inch shank spacing with 7/8" shanks.
- 2-1/2" x 2-1/2" x 3/16" wall frame.
- 3" x 2" x 3/16" cross members.
- · Optional gauge wheels.
- Gauge wheel tires 4.8" x 8", 4 ply.
- Category I three point hitch.
- 26-1/2" between shank row beams.
- Uses 47° sweeps with ½" plow-bolts on 1-¾" centers.
- · Solid shank mount.
- · Can accept sweeps up to 11" wide.
- Under-frame clearance 21-1/2".
- · Maximum working depth is 8".
- Gauge wheels offer good depth control.
- · Rated for tractors up to 65 HP.
- Approx. unit weights 5.25' 360 lb, 6.75' 465 lb, 8.25' 565 lb.
- Weight of gauge wheels 60 lb.
- 3 Year Limited Warranty
- 5 Year Shank Breakage Warranty


3-POINT HITCH CULTIVATOR			
MODEL	DESCRIPTION	NO. OF SHANKS	PART NUMBERS
5.25'	5.25' Frame Assembly c/w shanks (less sweeps)	7	1077
6.75'	6.75' Frame Assembly c/w shanks (less sweeps)	9	1078
8.25'	8.25' Frame Assembly c/w shanks (less sweeps)	11	1091

OPTIONAL EQUIPMENT	PART NUMBERS
Extension kit to make the 5.25' unit a 6.75' width	1160
Extension kit to make the 5.25' unit a 8.25' width	1161
Gauge Wheel Kit	1079
Sweeps. 11"	1131
Plow Bolts	1166
Universal Quick Hitch Adaptor	1077-03

Universal Quick Hitch Adaptor

PART NUMBER 1077-03

For use with the Model 1000 3 point hitch cultivator when fitting it to a Universal Quick Attachment bracket







Box 159 St. Brieux, Saskatchewan, SOK 3V0 Canada

P: 306.275.2155 **F:** 306.275.2101



